

INSULATION RESISTANCE METERS

MIC-10 and MIC-30



CAT IV
600V

IP 67



Wireless data
transmission to a computer.
Radio USB interface included!

- **Insulation resistance measurement:**

- selected test voltage: 50, 100, 250, 500, 1000V (MIC-10) or any voltage in the 50...1000V range with 10V step (MIC-30),
- automatic measurement in sockets with the UNI-Schuko adapter (MIC-30) with possibility of configuring pairs of measured cables,
- continuous indication of insulation resistance or leakage current,
- automatic discharge of capacitance of tested object after the insulation resistance measurement,
- acoustic signalling of five-second periods to facilitate obtaining time characteristics,
- measured test times T1, T2 i T3 to measure one or two absorption coefficients in the 1... 600 sec. range (only MIC-30),
- indication of actual test voltage during the measurement,
- protection against measuring live objects,
- three-lead measurement.

- **Continuity measurement of protective and equipotential conductors according to EN 61557-4 with the >200mA current**

- **Low-voltage circuit continuity and resistance measurement:**

- circuit resistance measurement (<1999 Ω) with the <15mA current,
- quick sound signal if circuit resistance is below 30 Ω .

- **Leakage current measurement (only MIC-30).**

- **Capacitance measurement during the R_{ISO} measurement**

- **Measurement of alternating and direct voltages in the 0...600V range.**

- **990 memory cells and wireless data transmission to a computer using the USB - OR-1 adapted (only MIC-30).**

- **Power supply: 4 AA disposable or rechargeable batteries, monitoring of power supply voltage.**

- **Meters conform to EN 61557.**

Sonel S.A.
ul. Wokulskiego 11
58-100 Świdnica
tel. +48 74 85 83 878
fax +48 74 85 83 808

dh@sonel.pl
www.sonel.pl

MIC-10 i MIC-30

Insulation resistance measurement

Measuring range according to EN 61557-2 for $U_i=50V$: 50k Ω ...250,0M Ω

Range	Resolution	Accuracy
0,0...999,9k Ω	0,1k Ω	±(3% m.v. + 8 digits) [±(5% m.v. + 8 digits)]*
1,000...9,999M Ω	0,001M Ω	
10,0...99,99M Ω	0,01M Ω	
100,0...250,0M Ω	0,1M Ω	

*- for the WS-04 lead (MIC-30)

Measuring range according to EN 61557-2 for $U_i=100V$: 100k Ω ...500,0M Ω

Range	Resolution	Accuracy
0,0...999,9k Ω	0,1k Ω	±(3% m.v. + 8 digits) [±(5% m.v. + 8 digits)]*
1,000...9,999M Ω	0,001M Ω	
10,00...99,99M Ω	0,01M Ω	
100,0...500,0M Ω	0,1M Ω	

*- for the WS-04 lead (MIC-30)

Measuring range according to EN 61557-2 for $U_i=250V$: 250k Ω ...2,000G Ω

Range	Resolution	Accuracy
0,0...999,9k Ω	0,1k Ω	±(3% m.v. + 8 digits) [±(5% m.v. + 8 digits)]*
1,000...9,999M Ω	0,001M Ω	
10,00...99,99M Ω	0,01M Ω	
100,0...999,0M Ω	0,1M Ω	
1,000...2,000G Ω	0,001G Ω	

*- for the WS-04 lead (MIC-30)

Measuring range according to PN-EN 61557-2 for $U_i=500V$:

- 500k Ω ...5,00G Ω (MIC-10)
- 500k Ω ...20,00G Ω (MIC-30)

Range	Resolution	Accuracy	
0,0...999,9k Ω	0,1k Ω	±(3% m.v. + 8 digits) [±(5% m.v. + 8 digits)]*	
1,000...9,999M Ω	0,001M Ω		
10,00...99,99M Ω	0,01M Ω		
100,0...999,0M Ω	0,1M Ω		
1,000...5,000G Ω	0,001G Ω	±(4% m.v. + 6 digits)	MIC-10
1,000...9,999G Ω	0,001G Ω	±(4% m.v. + 6 digits)	
10,00...20,00G Ω **	0,01G Ω	[±(6% m.v. + 6 digits)]*	MIC-30

*- for the WS-04 lead (MIC-30)

** - for the WS-04 lead – range to 10G Ω

Measuring range according to EN 61557-2 for $U_i=1000V$:

- 1000k Ω ...10,00G Ω (MIC-10)
- 1000k Ω ...100,00G Ω (MIC-30)

Range	Resolution	Accuracy	
0,0...999,9k Ω	0,1k Ω	±(3% m.v. + 8 digits)	
1,000...9,999M Ω	0,001M Ω		
10,00...99,99M Ω	0,01M Ω		
100,0...999,0M Ω	0,1M Ω		
1,000...5,000G Ω	0,001G Ω	±(4% m.v. + 6 digits)	MIC-10
5,00...10,00G Ω	0,01G Ω		MIC-10
1,000...9,999G Ω	0,001G Ω		MIC-30
10,00...99,99G Ω	0,01G Ω		MIC-30
100,00G Ω	0,1G Ω		MIC-30

„m.v.” measured value.

Continuity measurement of protective and equipotential conductors with the 200mA current
Measuring range according to EN 61557-4: 0,10...1999 Ω

Range	Resolution	Accuracy
0,00...19,99 Ω	0,01 Ω	±(2% m.v. + 3 digits)
20,0...199,9 Ω	0,1 Ω	
2000...1999 Ω	1 Ω	±(4% m.v. + 3 digits)

- Voltage on open terminals: <8V
- Output current at $R < 2\Omega$: $I_{sc} > 200mA$; $I_{sc} > 200mA$
- Compensation of test leads' resistance
- MIC-30 – bidirectional current flow, average resistance value is displayed
- MMIC-10 – unidirectional current flow

Low-voltage and resistance measurement

Range	Resolution	Accuracy
0,0...199,9 Ω	0,1 Ω	±(3% m.v. + 3 digits)
200...1999 Ω	1 Ω	

- Voltage on open terminals: <8V
- Current for closed terminals 5mA < ISC < 15mA
- Sound signal and green LED on when measured resistance < 30 Ω ± 50%
- Compensation of test leads' resistance,

Capacitance measurements

Range	Resolution	Accuracy
1...999nF	1nF	±(5% m.v. + 5 digits)
1,00...9,99 μ F	0,01 μ F	

- Capacitance value displayed during the R_{iso} measurement
- For test voltages below 100V and measured resistance below 10M Ω , unspecified capacitance measurement error

Measurement of alternating and direct voltage

Range	Resolution	Accuracy
0,0...299,9V	0,1V	±(2% m.v. + 6 digits)
300...600V	1V	±(2% m.v. + 2 digits)

- Frequency range: 45...65Hz

Standard accessories:

- MIC-30 Test lead with banana plug; 1,2m; red
- MIC-30 Test lead with banana plug; 1,2m; blue
- MIC-30 Shielded test lead with banana plug; 1,2m; black
- MIC-30 "Crocodile" clip K02; blue
- MIC-30 Receiver – interfejs for radio transmission OR1 (USB)
- MIC-10 Test lead with banana plug; 1,2m; black
- MIC-10 Test lead with banana plug; 1,2m; red
- MIC-10 "Crocodile" clip K01; black
- Pin probe with banana connector; black
- Pin probe with banana connector; red
- Carrying case M6
- Hanging straps
- Handle to suspend the meter
- Certificate calibration
- Battery set

- WAPRZ1X2REBB
- WAPRZ1X2BUBB
- WAPRZ1X2BLBBE
- WAKROBU20K02
- WAADAUSBOR1
- WAPRZ1X2BLBB
- WAPRZ1X2REBB
- WAKROBLK01
- WASONBLOGB1
- WASONREOGB1
- WAFUTM6
- WAPZSZE4
- WAPZOZUCH1

Additional accessories:

- Test lead with banana plug 5m; red
- Test lead with banana plug 5m; blue
- Shielded test lead with banana plug; 5m; black
- Test lead with banana plug 1,2m; blue
- "Crocodile" clip K02; red
- "Crocodile" clip K01; black
- "Crocodile" clip K02; blue
- Pin probe with banana connector; blue
- Adapter WS-04 with UNI-Schuko
- MIC-30 Software for creation of documentation from electrical measurements "SONEL Reports"

- WAPRZ005REBB
- WAPRZ005BUBB
- WAPRZ005BLBBE
- WAPRZ1X2BUBB
- WAKRORE20K02
- WAKROBL20K01
- WAKROBU20K02
- WASONBUOGB1
- WAADAWS04
- WAPROSONPE4

Electric safety:

- type of insulation double, according to EN 61010-1 and IEC 61557
- measurement category IV 600V (III 1000V) according to EN 61010-1
- protection class acc. to EN 60529 IP67

Other technical data:

- power supply 4 alkaline batteries or or battery package Ni-MH
- weight ~1kg
- dimentions 220 x 100 x 60 mm