

Iris Power Epoxy Mica Capacitors (80 pF)

Partial Discharge Sensors for Testing High Voltage Electrical Equipment

The durable Iris Power Epoxy Mica Capacitors (EMCs) are designed to detect Partial Discharge (PD) activity in electrical equipment (AC motors, generators, switchgear and dry-type transformers) while not imposing on the machine's operation or reliability in any way.

Iris Power EMCs are permanently installed (minimum one per phase) as close as possible to the equipment to be monitored to maximize sensitivity. In order to improve noise separation, the Iris Power EMCs are installed directionally or differentially, depending on the equipment.

Iris Power's 80pF EMCs are designed to block the 50/60Hz power frequency and allow only high frequency (>40MHz) signals to pass through, be collected and analyzed by an appropriate Iris Power portable instrument or continuous monitor.

PD monitoring is applicable to diverse equipment installations. That is why Qualitrol-Iris Power offers four different voltage-rated EMCs – 6.9kV, 16kV, 25kV and 28kV. The choice of which couplers to install is dependent on the operating voltage of the equipment.

UNIQUE FEATURES

Mica Splittings Dielectric

Iris Power EMCs are safe for use in operating equipment because they have excellent electrical properties due to an 80 mm (3 inch) layer of epoxy impregnated mica splittings as the main dielectric. In comparison, a typical 13.8kV stator coil has only about 3 mm (0.118 inch) thickness of epoxy mica paper.

Voltage Endurance Testing

Independent voltage endurance testing (IEEE 1043) proved that the 16kV Iris Power EMC withstands over 1000 hours at 30kVrms. According to statistical methods (IEEE 930-1987), this translates into 60,000 years of use at normal operating voltage. By comparison, the average 13.8kV coil is expected to withstand only 400 hours of exposure to 30kVrms. The Iris Power EMC's excellent endurance and thermal stability is due to the use of mica splittings, as opposed to mica paper or ceramics.



Over 40,000 Iris Power Epoxy Mica Capacitors are in service around the world, and have accumulated tens-of-millions of hours of reliable operation.



Iris Power EMCs are sold individually or in coupler kits complete with all installation materials including the silicone rubber insulating boot (EMC boot) shown here. Where required, insulating tapes are available.

IRIS POWER EPOXY MICA CAPACITORS (80 pF)

EMC VOLTAGE RATING				
	6.9 kV	16 kV	25 kV	28 kV
DEV @ 1pC (kV)	8	15	25	28
AC Hipot (kVrms)	15	33	51	57
Mass (kg)	1.1	1.6	2.3	2.3
Height	95mm (3.75")	127mm (5.0")	206mm (8.1")	206mm (8.1")
Diameter	89mm (3.5")	89mm (3.5")	89mm (3.5")	89mm (3.5")

DC AND IMPULSE CAPABILITY (BIL)

Iris Power EMCs have been independently tested to DC hipot and lightning impulse strengths far greater than any other apparatus in its voltage class. For example, Iris Power 16kV EMCs have passed:

- 150kV DC hipot (50kV required by ANSI C37.20.2)
- 150kV impulse (95kV required by ANSI C37.20.2)

HAZARDOUS LOCATIONS

The Iris Power EMCs can be used with Iris Power instruments certified for hazardous locations provided that they are installed in the appropriate enclosure to comply with the ATEX directive or UL certification for hazardous locations.

RADIATION ENVIRONMENTS

Iris Power EMC kits with installation material according to IEEE 323-1983 for Nuclear Power Generating Stations are available.

OTHER SPECIFICATIONS

- Mica Splittings Dielectric
- Voltage endurance tested (IEEE 1043) to >1000 hours at 30kVrms (16kV EMC)
- Capacitance rating: 80pF +/- 4pF
- Dissipation factor: 0.10%
- PDEV Sensitivity: 1 pC (ASTM D1868 and IEC 60270)
- Bandwidth: (-3dB); 40MHz to 350MHz
- Operating temperature range: -50°C to +130°C (-58°F to +266°F)
- Electrical Tracking Resistant (ANSI/IEEE C37.20.2)
- Calculated 60,000 year life (tested to IEEE 930-1987)
- Thermal Cycle Testing to -40°C to +150°C

Iris Power Epoxy Mica Capacitors is a trademark of Qualitrol-Iris Power.

QUALITROL-IRIS POWER HAS BEEN THE WORLD LEADER IN MOTOR AND GENERATOR WINDING DIAGNOSTICS SINCE 1990, PROVIDING A FULL LINE OF ON-LINE AND OFF-LINE TOOLS, AS WELL AS COMMISSIONING AND CONSULTING SERVICES.



A **QUALITROL** Company

www.irispower.com

www.qualitrolcorp.com

Iris Power LP
3110 American Drive
Mississauga, ON, Canada L4V 1T2
Phone: +1-905-677-4824
Fax: +1-905-677-8498
Sales.iris@qualitrolcorp.com

Qualitrol Company LLC
1385 Fairport Road
Fairport, NY, USA 14450
Phone: +1-585-586-1515
Fax: +1-585-377-0220



QUALITROL
Defining Reliability

Ver 13 • 1/12